



	RS2-4	RS3-5	RS4-6	RS4-9	RS8-14	RS10-20	RS13-20	RS20-30
Carrier Weight in Tons	2.4 - 4	3.5 - 5.5	4.4 - 6.6	4.4 - 10	8.8 - 15.5	11 - 22	14.3 - 22	22 -33
Average out put in Tons	9	11	16	27	35	44	60	100
Shafts	3	3	3	4	5	5	6	8
Bucket Capacity in Cubic yards	.16	.2	.26	.39	.52	.85	1.18	1.57
Hydraulic Requirements	10.57gpm 70-180bar	11.89gpm 70-180bar	13.21gpm 70-180bar	14.53gpm 70-180bar	16.92gpm 70-180bar	18.50gpm 70-180bar	26.42gpm 70-180bar	37.00gpm 70-180bar
Bucket Weight	551lbs	617lbs	750lbs	1014lbs	1356lbs	2337lbs	2756lbs	3748lbs
Working width	25.19"	32.48"	41.57"	41.57"	45.28"	49.60"	49.60"	49.60"
Overall width	35.83"	42.13"	51.18"	51.18"	55.20"	61.42"	65.34	65.34



1.203.457.9257 USA

INFO@AANDDEQUIPMENT.COM

SERVING NORTH AMERICA